



- NOTES:
- (7) CUT EXISTING WIRE AND RECONNECT AS SHOWN.
 - (6) MANUFACTURING TO DRILL HOLES THROUGH PLASTIC AND STEEL PLATE.
 - (5) FASTEN PART ASM TO SHROUD USING TAPE 76322-03-000.
 - (4) FACE OF MONITOR TO BE TOWARDS DRIVER, APPROX 45° OFF CENTER.
 - (3) ALIGN TV SYSTEM WITH CENTER OF SHROUD OPENING.
 - (2) RUN CABLE THRU LEFT HAND COVE TO FRONT OF UNIT.
 - (1) PARTS SUPPLIED WITH CAMERA KIT P/N 93040-02-000.

WINNERAGO		90 N-BODY
QTY IN	UNSPECIFIED TOLERANCES ARE:	MATERIAL
CHRP	ANGLE DIM (IN)	+ 1.5
DR	ONE-PLACE (IN.XI)	+ 0.5
PL	NO-PLACE (IN.XXX)	
DR	ANGLE	
CDR	THRU HOLE PROJECTION	
LAND	---	TITLE
NO	---	MONITOR INSTL
DIA #	SCALE: NONE	DO NOT SCALE DRAWING
ALL DIMENSIONS ARE IN MILLIMETERS	SHEET 1 OF 2	DATE 11/01/02

