



- Ⓐ VENT PIPE MUST PROJECT 51 MM MIN TO 64 MM MAX ABOVE ROOF FOR PROPER FIT AND FUNCTION.
- Ⓙ SEE DWG 61607-01-000 FOR INSTL OF GROMMET.
6. SEAL ALL AROUND SHOWER PAN WITH SILICONE 78474-01-CHT.
5. FOR CAN UNITS EACH HOLDING TANK SHALL HAVE A CSA APPROVAL STAMPED NEAR THE IAPMO APPROVAL.
4. ALL EXTERIOR OPENINGS AROUND PIPE TO BE SEALED WITH 69637-01-000.
3. ALL PIPE AND FITTINGS TO BE ASSEMBLED WITH SOLVENT 4020-01-000.
2. SLOPE OF TRAP ARM MUST BE 6 PER 305 MIN.
1. SLOPE OF HORIZONTAL PIPING TO BE 6 PER 305 MIN.

WINNERAGO 90 W/1F426RT

QTY	UNSPECIFIED TOLERANCES ARE:	MATERIAL
CHDR	WHOLE DIM (1) 1/4	
PIPE	ONE-PLACE (1) .01	
FLG	TWO-PLACE (1) .003	
ANG	ANGLE	
CDR	INDIC. WHOLE PROJECTION	

DRAINAGE SYSTEM INSTL

WINNERAGO

90 W/1F426RT

SCALE: 1:1

ALL DIMENSIONS ARE IN MILLIMETERS

SHEET 1 OF 1

DATE 09/10/09

