



- ⑦ NOT USED W/EUROPEAN EXPORT PACKAGE. ADD CONNECTOR LINE BETWEEN ELBOWS.
 - ⑥ USE STAPLE 8408-01-000 TO ATTACH TO SIDEWALL.
 - ⑤ CAP SEAL; SEE SEALANT MANUAL.
 - ④ USE WITHOUT EXTERIOR SHOWER.
3. ALL TUBING TO BE SECURED AT 1219 MAXIMUM SPACING WITH CLAMP 10495-01-000 AND SCREW G67-10-12B.
2. PLASTIC FITTINGS TO BE SEALED WITH SEALANT 84456-01-000.
1. TUBING TO BE INSTALLED WITH SUFFICIENT SLOPE TO PROVIDE DRAINAGE TO NEAREST VALVE.

LEGEND	
HOT LINE	-----
COLD LINE	-----

DATE	10/5/13
REV	
BY	
CHECKED	
DATE	
REVISION RECORD	

UNSPECIFIED TOLERANCES ARE:	MATERIAL:
WELD DIM (IN)	F 1
ONE-PLATE (IN)	F 1
TWO-PLATE (IN)	F 1
ANGLE	F 1
ROUND	F 1
THRU HOLE PROJECTION	F 1

WINNACOR 92 W/1C422RG2

422RG2 TITLE: WATER SYSTEM INSTL

SCALE: 0:1 DO NOT SCALE DRAWING SIZE: 11x17

DATE: 10/5/13

REF: 96804