



- (2) USE WITHOUT SURROUND.
  - (8) USE WITH SURROUND.
  - (7) SECURE VENT TUBES TO FLOOR.
  - (6) VENT PIPE MUST PROJECT 51" MINIMUM TO 64" ABOVE ROOF FOR PROPER FIT AND FUNCTION.
  - (5) SEE DRAWING 61607-01-000 FOR INSTALLATION OF GROMMET.
4. ALL EXTERIOR OPENINGS AROUND PIPE TO BE SEALED.
  3. ALL PIPE AND FITTINGS TO BE ASSEMBLED WITH SOLVENT 4020-01-000.
  2. SLOPE OF TRAP ARM MUST BE 6 PER 305.
  1. SLOPE OF HORIZONTAL PIPING TO BE 6 PER 305.

**WINNERS** 92 W/F424RC

DATE	UNSPECIFIED TOLERANCES ARE:	MATERIAL
DRWG	WHOLE DIM (IN)	1/8"
REV	ONE-PLACE (IN.XX)	1/32"
FILE	TWO-PLACE (IN.XXX)	1/64"
DATE	THREE-PLACE (IN.XXX.X)	1/128"
DRWG	THIRD-ANGLE PROJECTION	

LANOT 424RC2 TITLE: DRAINAGE SYSTEM INSTL  
 DIA # SCALE: NONE DO NOT SCALE DRAWING  
 ALL DIMENSIONS ARE IN MILLIMETERS SHEET 1 OF 1 106942

