



- ⑧ USE WITH DOUBLE CONTROL FAUCET.
- ⑦ USE WITH SINGLE CONTROL FAUCET.
- ⑥ USE WITHOUT EXTERIOR SHOWER.
- ⑤ USE WITH EXTERIOR SHOWER.
- ④ LOCATE LUMBER TO SUPPORT WATER HEATER.

3. ALL TUBING TO BE SECURED AT 1200 INTERVALS MAX WITH CLIP 91951-01-000 AND SCREW G13-06-16W.
2. TUBING TO BE INSTALLED WITH SUFFICIENT SLOPE TO PROVIDE DRAINAGE TO NEAREST VALVE.
1. PLASTIC FITTINGS TO BE SEALED WITH SEALANT 84456-01-000.

LEGEND

HOT	—————
COLD	—————

WINNEBAGO 92 W/IKG34R0

DATE	UNSPECIFIED TOLERANCES ARE:	MATERIAL
CHGR	FRAC DEC IN	FRAC DEC IN
P/E	1/16-PLACE IN 1/32	1/16-PLACE IN 1/32
W/E	1/16-PLACE IN 1/32	1/16-PLACE IN 1/32
DRGR	1/16-PLACE IN 1/32	1/16-PLACE IN 1/32

LAYOUT G34R02 TITLE: WATER SYSTEM INSTL
 SHEET 1 OF 3

WINNEBAGO WATER SYSTEM INSTL 105780



