



- 10 PRESSURE VALVE MUST BE BETWEEN THE WATER HEATER
- ⑨ ADD CONNECTOR LINE WHEN WATER HEATER IS REMOVED WITH EUROPEAN EXPORT PACKAGE.
 - ⑧ NOT USED WITH EUROPEAN EXPORT PACKAGE.
 - ⑦ USE WITH EXTERIOR SHOWER.
 - ⑥ USE WITHOUT EXTERIOR SHOWER OPTION.
 - ⑤ MOUNT SHIELD TO HEATER FLANGE ABOVE EXHAUST VENT.
 - ④ USE WITHOUT BYPASS.
3. ALL TUBING TO BE SECURED AT 1219 SPACING MAXIMUM WITH CLAMP 10495-01-000 AND SCREW 667-10-128.
2. PLASTIC FITTINGS TO BE SEALED WITH SEALANT 84456-01-000.
1. TUBING TO BE INSTALLED WITH SUFFICIENT SLOPE TO PROVIDE DRAINAGE TO NEAREST VALVE.

LEGEND	
HOT	-----
COLD	-----

WINNEBAGO 92 W/ICF27EC

DATE	UNSPECIFIED TOLERANCES ARE MATERIAL
CHKD	SHOLE DRN 101
DATE	ONE-PLACE 19 81
DATE	ONE-PLACE 19 801
DATE	ANGLE
DATE	TRUSS W/ANGLE PROJECTION
DATE	TRUSS W/ANGLE PROJECTION

LABOR # F27EC2 TITLE: WATER SYSTEM INSTL

WINNCO

DATE SCALE 0 1 30 NET SCALE DRAWING SIZE 1 1/8
 ALL DIMENSIONS ARE IN MILLIMETERS SHEET 1 OF 2 102029

- COMPT ASM-SHOWER, EXTERIOR
106217-01-CHT
EXTR
2754-51-005(2)
SCREW
G39-08-12B(4)
SHOWER HEAD
103092-01-000
103092-02-000
FAUCET
79563-03-CHT

