



- (A) VENT PIPE MUST PROJECT 51 MM MIN TO 64 MM MAX ABOVE ROOF FOR PROPER FIT AND FUNCTION.
 - (A) SEE DWG 61607-01-000 FOR INSTL OF GROMMET.
 - (A) SEAL ALL AROUND SHOWER PAN WITH SILICONE 78474-01-CHT.
5. FOR CANADIAN UNITS EACH HOLDING TANK SHALL HAVE A CSA APPROVAL STAMPED NEAR THE IAPMO APPROVAL.
 4. ALL EXTERIOR OPENINGS AROUND PIPE TO BE SEALED WITH 69637-01-000.
 3. ALL PIPE AND FITTINGS TO BE ASSEMBLED WITH SOLVENT 4020-01-000.
 2. SLOPE OF TRAP MUST BE 6 PER 300 MINIMUM.
 1. SLOPE OF HORIZONTAL PIPING TO BE 6 PER 300 MINIMUM.

WINNEMAGO 94 F33R0	
DATE	UNSPECIFIED TOLERANCES ARE MATERIAL
CHG	SCALE OR 1:1
REV	ONE-PLACE IN 31
FILE	TWO-PLACE IN 301
FILE	ANGLE
CDR	TRUSS W/OLE PROTECTION
LAYOUT F33R04	TITLE: DRAINAGE SYSTEM INSTL
REV 1	DO NOT SCALE DRAWING
REV 2	FILE NO
REV 3	DATE
REV 4	SHEET 1 OF 1
REV 5	110912

