



- Ⓐ VENT PIPE MUST PROJECT 51 MM MIN TO 64 MM MAX ABOVE ROOF FOR PROPER FIT AND FUNCTION.
 - Ⓙ SEE DWG 61607-01-000 FOR INSTL OF GROMMET.
 - Ⓚ SEAL ALL AROUND SHOWER PAN WITH SILICONE 78474-01-CHT.
5. FOR CANADIAN UNITS EACH HOLDING TANK SHALL HAVE A CSA APPROVAL STAMPED NEAR THE IAPMO APPROVAL.
 4. ALL EXTERIOR OPENINGS AROUND PIPE TO BE SEALED WITH 69637-01-000.
 3. ALL PIPE AND FITTINGS TO BE ASSEMBLED WITH SOLVENT 4020-01-000.
 2. SLOPE OF TRAP MUST BE 6 PER 300 MINIMUM.
 1. SLOPE OF HORIZONTAL PIPING TO BE 6 PER 300 MINIMUM.

WINNACGO 94 F33R0

QTY	UNSPECIFIED TOLERANCES ARE MATERIAL
CHP	WELD DIM 1/2"
PT	ONE-PLATE 1/4 X 1/2"
PL	TWO-PLATE 1/4 X 1/2"
W	WELD
CDR	TRUSS W/OLE PROTECTION

LAINT F33R04 TITLE: DRAINAGE SYSTEM INSTL
 REF: 106419 110912

