



- ⑥ USE WITHOUT MOTOR AID.
- ⑤ USE WITH EXTERIOR SHOWER.
- ④ USE WITH MOTOR AID.

3. ALL TUBING TO BE SECURED AT 1200 INTERVALS MAX WITH CLAMP 10495-01-000 OR CLIP 91951-01-000 AND SCREW G67-10-12B.
2. TUBING TO BE INSTALLED WITH SUFFICIENT SLOPE TO PROVIDE DRAINAGE TO NEAREST VALVE.
1. PLASTIC FITTINGS TO BE SEALED WITH SEALANT 84456-01-000.

NOTES:

X-X FOR WATER CALLOUTS SEE DWG NO. 116230-01-000

LEGEND

HOT	-----
COLD	-----

		97 429WU
DATE	UNDESIGNED TOLERANCES ARE:	MATERIAL
DATE	WHOLE DIM (IN)	F.F.
DATE	ONE-PLACE (IN.XI)	F.F.
DATE	TWO-PLACE (IN.XXX)	F.F.
DATE	MIXED	F.F.
DATE	THIRD WHOLE	F.F.
DATE	PRODUCTION	F.F.
DATE	DATE	DATE
DATE	DATE	DATE
DATE	DATE	DATE

DRAWING NO. 429WU TITLE: WATER SYSTEM INSTL
 SHEET 1 OF 2 REF: 122573 A 1
 SCALE: 0.2
 ALL DIMENSIONS ARE IN MILLIMETERS
 SHEET 1 OF 2
 123097

- WATER HEATER
- 51391-01-000
- (MANUAL IGNITION)
- 51391-02-000
- (ELECTRONIC IGNITION)
- 51391-03-000
- (W/MOTOR AID)
- DOOR
- 78506-01-CHT
- AL EXTR
- 2726-01-210
- 2726-01-212(2)
- SCREW
- G39-10-169(18)
- SEALANT

