




DANGER

Danger of electrical shock, burns or death. Always remove all power sources before attempting any repair, service or diagnostic work. Power can be present from shore power, generator, inverter or battery. All power sources must be disabled and secured before performing any service.



CAUTION

If you lack the skills, tools or equipment to perform diagnostic or repair work leave such work to an authorized Winnebago Industries dealer or other qualified shop.



- NOTES:
- △ 8 SEE WIRING DIAGRAM-BODY, 12V FOR ADDITIONAL INFORMATION.
 - △ 7 SEE MANUFACTURERS DIAGRAM.
 - △ 6 WIRE ROUTED BELOW FLOOR.
 - △ 5 ONLY WITH (1L1)
 - △ 4 WIRE ROUTED THRU ROOF.
 - △ 3 WIRE ROUTED THRU SIDEWALL.
 - △ 2 WIRE ROUTED THRU FLOOR.
 - △ 1 ALL OUTLETS DOWN STREAM AND INCLUDING THIS OUTLET ARE GROUND FAULT CIRCUIT INTERRUPT PROTECTED.

- (39A) EXT RECEPTACLE DPLX 120VAC
- (1L1) TV-27" W/VIDEO SELECTION SYS
- (1JR) TV-13" W/DVD-12V
- (12D) ELECTRICAL SYSTEM 30 AMP
- (265) CODES/STANDARDS-CSA/CMVSS
- (1B1) CODES/STANDARDS-USA

WINNEBAGO		COPYRIGHT 2006 WINNEBAGO INDUSTRIES, INC.	
DFTR	ORIG. DATE		
CHKR	ALL DIMENSIONS ARE IN MILLIMETERS		
P.E.	FIRST USED	07 229T	
M.E.			
DSNR			
UNSPECIFIED TOLERANCES ARE:		MATERIAL:	
WHOLE DIM (X)	:		
ONE-PLACE (X.X)	:		
TWO-PLACE (X.XX)	:		
ANGLE	:		
THIRD ANGLE PROJECTION			
DO NOT SCALE DRAWING			
TITLE: WIRING DIAGRAM-BODY, 110V			
SHEET 1 of 1	PART NO	157277	REV
REF:	1 6/17/2006		