

8

7

6

5

4

3

2

1



D

D

C

C


B

B

A

A

CABLE ASM-CHASSIS BATTERY (RED)	141415-37-018	3
CABLE ASM-COACH BATTERY (YEL)	141415-52-019	
CABLE ASM-COACH BATTERY GND (BLK)	133567-12-007	
CABLE ASM-GENERATOR (GRN)	141415-42-039	3
CABLE ASM-GENERATOR GND (BLK)	133566-12-005	3
CABLE ASM-FRAME GND	133566-12-003	



265 CODES/STANDARDS-CSA/CMVSS

1B1 CODES/STANDARDS USA

1B1 265



COPYRIGHT 2016 WINNEBAGO INDUSTRIES, INC.

DSNR:		ALL DIMENSIONS ARE IN MILLIMETERS		
DFFR:		MATERIAL:		
UNSPECIFIED TOLERANCES:				
WHOLE DIM (X)	± 3			
ONE-PLACE (X.X)	± 1.5			
TWO-PLACE (X.XX)	± 0.50			
ANGLE	± 1°			
REFER TO ES0018 FOR FASTENER TIGHTENING GUIDELINES		WEIGHT: (LBS)	FIRST USED:	
DESCRIPTION: BATTERY INSTL				
SHEET:	ITEM/PART NO.:	REF:		REV
1 OF 2	000012316 / 31144202000	1		19-Sep-2016



ROUTING OF CABLE SHOWN IN WIRING INSTL-CHASSIS ONLY.

2. BATTERY CABLES ARE NOT TO BE ROUTED OVER BATTERY FILL CAPS.

1. SEE WIRING INSTL-CHASSIS FOR ADDITIONAL INFORMATION.

NOTES:

FOR ELECTRICAL TORQUE SPECIFICATIONS SEE DWG NO. 128783-01-000

FOR ELECTRICAL CALLOUTS SEE DWG NO. 121339-01-000

8

7

6

5

4

3

2

1

