



- 215 DISHWASHER WITHOUT
- 214 DISHWASHER DRAWER STYLE
- 265 CODES/STANDARDS-CSA/CMVSS
- 1B1 CODES/STANDARDS USA



DSNR:	ALL DIMENSIONS ARE IN MILLIMETERS	
DFFR:		
UNSPECIFIED TOLERANCES:		MATERIAL:
WHOLE DIM (X) :	3	
ONE-PLACE (X.X) :	1.5	
TWO-PLACE (X.XX) :	0.50	
ANGLE :	1°	
REFER TO ES0018 FOR FASTENER TIGHTENING GUIDELINES	WEIGHT: (LBS)	FIRST USED:
		18 P42Q

LOAD CENTER ASM		
SHEET: 1 OF 1	ITEM/PART NO: 000035710 / 31807701000	REV:
REF: 1		06-Jan-2022

- NOTES:**
- 5 BLACKEN OUT TAILGATE WITH BLACK MARKER.
 - 4 BLACKEN OUT AWNING WITH BLACK MARKER.
 - 3 BLACKEN OUT DISHWASHER WITH BLACK MARKER WITH FEATURE 215
 - 2. REMOVE 400MM FROM OUTER JACKET ON ALL WIRES ENTERING LOAD CENTER AND TRIM INDIVIDUAL CONDUCTORS AS REQUIRED TO MAKE INTERNAL CONNECTIONS
 - 1. ALL GROUND WIRES TO BE COVERED WITH TUBING 8041-02-000.

FOR ELECTRICAL TORQUE SPECIFICATIONS SEE DWG NO. 128783-01-000

FOR ELECTRICAL CALLOUTS SEE DWG NO. 121339-01-000