



DETAIL AA

- 8 SEE WIRING INSTL.-BODY,110V FOR ADDITIONAL INFORMATION.
  - 7 MAIN WIRE WILL BE INSTALLED ON THE PRODUCTION LINE.
  - 6 SEE DETAIL AA FOR LABELING.
  - 5 SEE WIRING INSTL-CHASSIS FOR ADDITIONAL INFORMATION.
  - 4 SEE WIRING INSTL-BODY,12V FOR ADDITIONAL INFORMATION.
  - 3 CONNECT BLACK WIRE FROM CONVENIENCE RECEPTACLE TO DEDICATED CIRCUIT BREAKER.
  - 2 ATTACH TO UNUSED SCREW HOLE ON BACK SIDE OF PANEL TO SECURE WIRES.
1. ALL GROUND WIRES TO BE COVERED WITH TUBING 8041-02-000.

NOTES:

FOR ELECTRICAL TORQUE SPECIFICATIONS SEE DWG NO. 128783-01-000

FOR ELECTRICAL CALLOUTS SEE DWG NO. 121339-01-000

- 265 CODES/STANDARDS-CSA/CMVSS
- 1B1 CODES/STANDARDS USA

1B1 265

**WINNEBAGO**  
COPYRIGHT 2016 WINNEBAGO INDUSTRIES, INC.

|  |                                       |
|--|---------------------------------------|
| DSNR:  | ALL DIMENSIONS ARE IN MILLIMETERS     |
| DFFR:  | MATERIAL:                             |
| UNSPECIFIED TOLERANCES:                            | WEIGHT: (LBS)                         |
| WHOLE DIM (X) ± 3                                  | FIRST USED: 18 423T                   |
| ONE-PLACE (X.X) ± 1.5                              |                                       |
| TWO-PLACE (X.XX) ± 0.50                            |                                       |
| ANGLE ± 1°   |                                       |
| REFER TO ES0018 FOR FASTENER TIGHTENING GUIDELINES |                                       |
| DESCRIPTION:                                       |                                       |
| <b>LOAD CENTER ASM</b>                             |                                       |
| SHEET: 1 OF 1                                      | ITEM/PART NO: 000118606 / 32248401000 |
| REF:   | 1 21-Nov-2017                         |