



DETAIL AA

- 9 GROUND T AND S ARE PART OF WIRE ASM-CHASSIS AND WILL BE INSTALLED ON THE PRODUCTION LINE.
- 8 SEE WIRING INSTL BODY, 110V FOR ADDITIONAL INFORMATION.
- 7 MAIN WIRE WILL BE INSTALLED ON THE PRODUCTION LINE.
- 6 SEE DETAIL AA FOR LABELING.
- 5 SEE WIRING INSTL-CHASSIS FOR ADDITIONAL INFORMATION.
- 4 SEE WIRING INSTL-BODY, 12V FOR ADDITIONAL INFORMATION.
- 3 CONNECT BLACK WIRE FROM CONVENIENCE RECEPTACLE TO DEDICATED CIRCUIT BREAKER.
- 2 ATTACH TO UNUSED SCREW HOLE ON BACK SIDE OF PANEL TO SECURE WIRES.

1. ALL GROUND WIRES TO BE COVERED WITH TUBING 8041-02-000.

NOTES:

- 265 CODES/STANDARDS-CSA/CMVSS
- 1B1 CODES/STANDARDS USA



DSNR:	ALL DIMENSIONS ARE IN MILLIMETERS	
DFFR:		
UNSPECIFIED TOLERANCES:	MATERIAL:	
WHOLE DIM (X) : 3		
ONE-PLACE (X.X) : 1.5		
TWO-PLACE (X.XX) : 0.50		
ANGLE : 1°		

REFER TO ES0018 FOR FASTENER TIGHTENING GUIDELINES

WEIGHT: (LBS) FIRST USED: 19 423F

DESCRIPTION: **LOAD CENTER ASM**

SHEET: 1 OF 1 ITEM/PART NO: 000157598 / 32705501000 REF: 1 22-May-2019

FOR ELECTRICAL TORQUE SPECIFICATIONS SEE DWG NO. 128783-01-000

FOR ELECTRICAL CALLOUTS SEE DWG NO. 121339-01-000

