WINNEBAGO

ACCESS / Specifications

	SINGLE AXLE				TANDEM AXLE						
WEIGHTS & MEASURES	**15RB**	**15BH**	**18RK**	**18DBH**	**25BH**	**25RK**	**25ML**	**26BH**	**26RL**	**28FK**	**30BH**
Exterior Length	21'3"	21'3"	22'6"	22'6"	29'11"	29'4"	29'	29'	30'1"	32'	33'2"
Exterior Height[1]	6'8"	6'8"	10'4"	10'4"	11'2"	11'2"	11'5"	11'5"	11'5"	11'5"	11'5"
Exterior Width[2]	8'	8'	8'	8'	8'	8'	8'	8'	8'	8'	8'
Awning Length	12'	12'	14'	14'	19'	16'	20'	20'	21'	21'	21'
Interior Height	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"
Freshwater Tank Capacity[3] (gal.)	49	49	49	49	60	60	60	60	60	60	60
Water Heater Capacity (gal.)	6	6	6	6	N/A	N/A	6	6	6	6	6
Holding Tank Capacity - Black[3] (gal.)	40	40	40	40	49	49	49	49	49	47	49
Holding Tank Capacity - Gray 1[3] (gal.)	40	40	40	40	49	2 @ 49	49	49	49	47	47
Holding Tank Capacity - Gray 2[3] (gal.)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	49	49
LP Capacity 1[4] (lbs.)	20	20	20	20	40	40	20	20	20	20	20
LP Capacity 2[4] (lbs.)	N/A	N/A	N/A	N/A	N/A	N/A	20	20	20	20	20
GVWR (lbs.)	5,100	5,100	5,100	5,100	8,800	8,800	8,800	8,800	8,800	8,800	8,800
Axles	5,100	5,100	5,100	5,100	2 @ 4,400	2 @ 4,400	2 @ 4,400	2 @ 4,400	2 @ 4,400	2 @ 4,400	2 @ 4,400
Dry Weight (lbs.)	3,516	3,496	3,900	3,850	6,456	6,520	6,472	5,700	6,454	6,790	7,146
Furnace (BTU)	18,000	18,000	18,000	18,000	30,000	30,000	30,000	30,000	30,000	30,000	30,000
Dry Hitch Weight (lbs.)	386	454	450	550	815	670	794	698	744	998	910
Hitch Height	22"	22"	22"	22"	22"	22"	22"	22"	22"	22"	22"
Tire Size	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E	225/75R15E
Sleeps[5]	3	5	4	5	7	5	5	6	5	5	7
							DEALER STOCK ONLY				

FOOTNOTES

1. The height of each model is measured to the top of the tallest standard feature and is based on the curb weight of a typically equipped unit. The actual height of our vehicle may vary by several inches depending on chassis or equipment variations. Please contact your dealer for further information.
2. Floorplans feature a wide-body design – over 96-inches. In making your purchase decision, you should be aware that some states restrict access on some or all state roads to 96-inches in body width. Before making your purchase decision, you should confirm the road usage laws in the states of interest to you.
3. Capacities are based on measurements prior to tank installation. Slight capacity variations can result due to installation applications.
4. Capacities shown are tank manufacturer's listed water capacity (W.C.). Actual filled LP capacity is 80% of listing due to overfilling prevention device on tank.
5. Sleeping capacity is the maximum based on a specific floorplan.

Because features, specification, equipment, and options may vary from those highlighted here, the buyer is responsible for confirming with the dealer the features, specifications, equipment, and options included in their specific vehicle.

In addition, Winnebago's program of continuous product improvement may result in changes to vehicle specifications, equipment, model availability, and price without notice.

Interior

Full-overlay European-style cabinetry
Carpetless slideouts
Roller shades
Versatile seating arrangements (depending on floorplan)

OPTIONAL EQUIPMENT

TV (15RB, 15BH, 18RK, 18DBH)

TANDEM AXLE

Tri-fold sofa (25BH)
Theater Seating (25RK)

Galley

Undermount stainless-steel sink

SINGLE AXLE

1 cu. ft. microwave
12-volt refrigerator
Recessed 2-burner cooktop w/backlit knobs
Range hood

TANDEM AXLE

1.1 cu. ft. convection microwave
10 cu. ft. 12-volt refrigerator
Recessed 3-burner cooktop w/backlit knobs
Range hood

Bath

Vanity mirror (select floorplans)
Under-sink storage
30" x 36" Shower w/door and large 14" x 22" skylight
Roof vent
Foot flush toilet

Bedroom

66" x 80" Olympic queen bed (25RK, 25BH)
60" x 80" Queen bed (15BH, 18RK, 18DBH)
Underbed storage
Wardrobe w/removable shelf
Versatile sleeping arrangements

Exterior

NXG engineered frame
Durable sidewall metal
15" load range E tires
Dexter® E-Z Lube® axles
Powered patio awning w/LED lighting
All LED exterior lighting
Fully enclosed underbelly w/radiant foil insulation
One-piece TPO roof membrane
Aerodynamic front profile
Rear back-up camera prep
Stabilizer jacks
Protected wheel wells
Weatherproof junction boxes
Solid entry step
Tinted/opening windows

TANDEM AXLE

Power tongue jack
2" accessory receiver w/350 lb. capacity
(2) 20 lb. LP tanks
Heated pass-through storage

Heating & Cooling

SINGLE AXLE

8,000 BTU roof A/C
18,000 BTU furnace

TANDEM AXLE

15,000 BTU ducted roof A/C
30,000 BTU furnace

TANDEM AXLE OPTIONAL EQUIPMENT

8,000 BTU ducted roof A/C w/50-amp upgrade

Electrical System

Winnebago® all-in-one control panel
USB/USBC charge ports

OPTIONAL EQUIPMENT

200-watt solar w/30-amp. charge controller

Plumbing System

1.5" freshwater drain

SINGLE AXLE

10-gallon water heater
Black tank flush

TANDEM AXLE

60,000 BTU
Black tank flush

Warranty

See your dealer for complete warranty information.